

CONCRETE STAIN & SUPPLY, LLC

Technical Data Sheet (TDS)

Stencil Spray

**This product may only be used on fully cured concrete. Allow a minimum of 28-45 days of cure time after the concrete is poured to allow ample time for the concrete to completely hydrate.

Product

A fast drying metal luster stencil spray that adds beautiful metallic effects and highlights to decorative concrete projects.

Coverage

Coverage rate is 5 - 25 square feet per 8 ounce container. Coverage variations depend on concrete surface porosity and amount of material applied.

Surface Preparation

Concrete must be clean and free of dirt, dust, oil, grease, mold and mildew, and any other contaminants. RAC Stained concrete must be neutralized, thoroughly cleaned, and dry prior to application.

Stir well before use! Metallic pigments settle out of suspension and require thorough stirring prior to application.

Application Tools

Aerosol Sprayer
HVLP Sprayer

Application

Apply desired Bello Stencil to the project and mist a fine spray of Stencil Stain over the open areas of the stencil. Spray in multiple very thin coats allowing the Stencil Spray to dry in between each application. As soon as the last coat of Stencil Spray is dry remove Bello Stencil from the project surface.

Highlights – To add a metallic sheen to decorative concrete surfaces, mist a light coat of Stencil Spray over the desired area.

Drying Time

Dry to touch: 5 - 15 minutes
Recoat: when dry to touch
Light Foot Traffic: 3 hours

Clean Up

Tools can be cleaned with Xylene or Acetone.

Storage and Shelf Life

Do not allow to freeze. Shelf life of unopened product is approximately one year.

Safety

DANGER: Flammable. Use only with adequate ventilation. Extinguish all pilot lights and ignition sources prior to use.

Always use appropriate safety equipment including but not limited to, goggles, face shield, rubber gloves, chemical resistant clothing or apron, and chemical respirator.

INHALATION: Vapors may cause dizziness, headaches, or nausea. Immediately move to fresh air. Seek medical attention.

EYES: Contact with eyes can cause severe burning, irritation, and blurred vision. Flush with water. Seek medical attention.

SKIN: May cause severe irritation and or chemical burns. Wash with soap and water. Seek medical attention.

Keep out of reach of children.

Use only with adequate ventilation.

Keep away from heat, sparks & flame. Vapors may cause fire. Avoid prolonged contact with skin. Use only with adequate ventilation. Avoid breathing vapors or spray mist. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Close container after use.

It is the sole responsibility of the property owner or applicator to determine the suitability and safety of applying this product in areas of pedestrian traffic.

Limitations

Do not apply when air or surface temperature exceeds 90 degrees (F) or LAP marking / poor penetration / bubbling may result. Do not apply to wet or damp concrete. Allow for extended dry times during cold weather / high humidity.

Warranty

The Manufacturer and/or the Seller warrants that if any goods supplied prove defective in workmanship or material, that Manufacturer and/or Seller shall replace them or refund the purchase price. This warranty is made in lieu of any and all other warranties expressed or implied. Before application, the User shall determine the suitability of the product for his intended use and User assumes all risks and liabilities whatsoever in connection therewith. Under no circumstances shall the Manufacturer and/or Seller be liable for incidental, consequential or other damages for alleged negligence, breach of warranty, or strict liability arising out of use or handling of this product. The sole liability of Manufacturer and/or Seller for any claims arising out of the use or sale of the product shall be for the User's purchase price. Any claim of defective product must be received in writing within one (1) year from date of shipment.

Prohibitions

Selected state and county jurisdictions prohibit or limit the use of solvent based products. Users should consult local guidelines before using this product.